

## 11KW Type 2 To Type 2 EV Charging Cable



LIA has been working in the field of EV Charging Cable for many years, and through independent research and development, we have mastered the main technology of the EV Chargers. Our 11KW Type 2 To Type 2 EV Charging Cables have a good price advantage and cover most of the European and Asian markets. We look forward to becoming your long-term partner in China.

High quality 11KW Type 2 To Type 2 EV Charging Cable is offered by China manufacturer LIA. LIA is a manufacturer specializing in EV Charging products include EV charging stations, EV cables and EV connectors. Meanwhile, we also offer product customization service upon the request in order to meet the local market preferences and needs.

### Our company

LIA strive to provide constantly updated products, perfect project solutions and efficient after-sales service to ensure our customers rank top in the market. We are committed to become the most professional EV charging equipment manufacturer in China and will keep working hard for it.

### FAST & RELIABLE CHARGING

LIA 11KW Type 2 To Type 2 EV Charging Cable provides your electric vehicle with fast and reliable charging for any domestic or home location.

### COMPATIBILITY & COMPLIANT

Compatible with all Type 2 (IEC62196) electric vehicles on the market and tested to meet CE certification requirements.

## WEATHER/HEAT RESISTANT

Recharging during all weather conditions is no problem with our LIA 11KW Type 2 to Type 2 Charging Cable. Our Charging Cable is also heat resistant, allowing you to charge your vehicle for longer periods.

- Adapter: IEC62196-2(Type 2)
- Certification: CE
- Nice appearance, hand-held ergonomic design, easy plug.
- Warranty : 2 years.

### Specification :

Product Model	EVP-M2F2-316
Color	Black / white / red / blue / gray
Rated Current	16A
Rated Voltage	AC 400V (three phase)
Charging Power	11KW
Mechanical life	unload plug & off >10000 times
Working Temperature	-30°C~65°C
Impact resistance	1m height drop and 2 Tons vehicle run over pressure
Insulation Resistance	>1000MΩ
Contact Resistance	0.5MΩ MAX
Protection Class	IP54
Contact Pin	Aluminum alloy, silver-plated surface, insulated top
Shell Material	Thermoplastic (flame retardant rating V-0)
Cable Length	5m (Length is optional, Straight line or Spring line is optional)



